



**ODYSSEY**  
THE EXTREME BATTERY

MARINE

GOLF

INDUSTRIAL

AUTO

SPECIAL APPLICATIONS

SOLAR

**EXTREME SERIES 34M-PC1500T**

**EXTREME POWER AND ENDURANCE**

• **MAINTENANCE FREE – AGM VALVE REGULATED**

- BCI Group 34M, 12V
- CCA 850 / MCA 1050 / PHCA 1500
- Reserve Capacity [min]: 135@25 A
- Reserve Capacity [Ah@20hr rate]: 68
- Weight: 49.50 lbs.
- Length- 10.85 in (275.60 mm)
- Width- 6.76 in (171.70 mm)
- Height- 7.82 in (198.6mm)



**ODYSSEY Extreme Series Marine Battery Model 34M-PC1500T**

**(Group 34 with tin-plated SAE posts, 3/8 inch positive and 5/16 inch negative thread SS stud terminals)**

Like an athlete that is both a sprinter and a long distance runner, the ODYSSEY Marine Dual Purpose battery has both massive starting power and amazing deep cycling capability - up to 400 cycles at 80% depth of discharge. With twice the overall power and three times the life of conventional marine batteries, the ODYSSEY battery is ideal for trolling, starting, and for powering the many on-board electronic accessories common in today's boats and recreational vehicles



# ODYSSEY

## THE EXTREME BATTERY

### Tin Alloy Coated Brass Terminals

Brass terminals coated with high-quality tin alloy ensure secure, corrosion-free cable connections

### Pure Lead Plates

Constructed from 99.99% pure virgin lead, ODYSSEY battery plates are extremely thin, so more of them can fit into the battery. More lead plates equals more power



### Robust Intercell Connections

Built to stringent specifications, cell connectors are casted to the plates, and bonded to resist vibration and eliminate internal sparking

### Available Metal Case

Selected ODYSSEY batteries are available with metal casing for high heat applications

### Why Use ODYSSEY Batteries

- **Better warranty**
  - Up to 4-year limited full replacement warranty — not pro rata.
- **Longer service life**
  - 3-10 years of service life to save you time, money, and aggravation
- **Longer cycle life**
  - 70% longer cycle life than conventional deep cycle batteries — high stable voltage for longer periods of time.
- **Longer shelf life**
  - Can be stored on open circuit (nothing connected to the terminals) without recharging for up to 2 years or 12.00V, whichever occurs first.
- **Faster recharge**
  - The highest recharge efficiency of any sealed lead battery on the market — capable of 100% recharge in 4-6 hours.
- **Mounting flexibility**
  - Non-spillable design — can be mounted on any side in any position except inverted.
- **Vibration resistance**
  - Design protects against high impact shock and mechanical vibration — a common cause of premature battery failure.
- **Extreme temperature tolerant**
  - Operating temperatures from -40°C (-40°F) to 45°C (113°F), for models without a metal jacket, and from -40°C (-40°F) to 80°C (176°F) for models with a metal jacket.
- **Totally maintenance free**
  - No need to add water, ever! Drycell design with resealable venting system.
- **Improved safety**
  - US Department of Transportation classified as a 'non-spillable' battery. No acid spills, no escaping gases.